

DIAMIND I LINE

PHYSICAL CONTAMINATION DETECTION + WEIGHT CONTROL

X-RAY + CHECKWEIGHERS

FOR SMALL AND MEDIUM HORIZONTAL PRODUCTS

HR - SR - HL - BR / EL-300 - EL-400 Series

TOP-DOWN X-RAY INSPECTION AND WEIGHT CONTROL

- · For unpackaged products or packaged in flow-pack, cases, trays, etc.
- · The best inspection solutions, together with high-precision weighing
- · All the advantages of the two single units
- · A single operator interface to control both inspections
- · Reduced costs and footprint compared to two separated machines
- · Same compliance with regulations as the single units

FEATURES

- An exclusive monoblock integrating weighing module and X-Ray inspection thanks to internal design of custom electronics
- Hygienic design, quick-removal conveyors, washable structure
- Separate ejection systems to keep the rejects distinguished
- Easy-opening doors for total acces to the inspection area




Easy-opening door



Control panel





DIAMIND | LINE Inspection





MODELS


| CODE | CONVEYORS WIDTH | WEIGHING RANGE | ACCURACY * | DISPLAY DIVISION |
|----------------|-----------------|----------------|------------|------------------|
| HR-600/EL-300 | 140-240 mm | 600 g | ± 0,2 g | 0,1 g |
| SR-1200/EL-300 | 240 mm | 1200 g | ± 0,2 g | 0,2 g |
| HL-3200/EL-300 | 240 mm | 3200 g | ± 0,2 g | 0,1 g |
| SR-1200/EL-400 | 320 mm | 1200 g | ± 0,2 g | 0,2 g |
| HL-3200/EL-400 | 320 mm | 3200 g | ± 0,5 g | 0,5 g |
| BR-6000/EL-400 | 320 mm | 6000 g | ± 1,0 g | 1,0 g |


* variable according to the type and weight of the product and the production speed

STANDARD TECHNICAL FEATURES

| Control panel | colour touchscreen 15" | |
|--------------------------------------|-----------------------------------|--|
| Data processing electronics | RISC embedded FPGA | |
| Generator | latest generation – up to 100 W – | |
| | electronic and integrated cooling | |
| | module, maintenance not requested | |
| Sensor | RISC embedded FPGA with | |
| | 0,8 mm pixel - IP65 | |
| Self-learning system and Calibration | included | |
| Data and images collection software | included through Ethernet and USB | |
| Kit for remote assistance | included | |
| Compliance industry 4.0 | with bidirectional protocol | |
| Conformity | CE, MID, BRC, IFS, HACCP, GMP | |
| Linear speed | up to 90 m/min | |
| Production | up to 450 ppm | |
| Protection degree | IP65 | |


LAYOUT






INSPECTION AREA

- product height
- product width





PACKAGING



















