VEGATRONIC 2000 ML

INTERMITTENT VERTICAL FORM, FILL & SEAL MACHINE



MAIN FEATURES

- 1 High-efficiency intermittent VFFS machine
- 2 Hygienic Open Frame Design
- 3 Extreme sealing pressure
- 4 Maximum versatility
- 5 Ultrasonic sealing option


IMA Ilapak's Vegatronic 2000 ML is today's most innovative and high-tech intermittent machine. Excellent sanitary design, great accessibility and a variety of pack styles including Doy-style pouches make this machine unique and ideal in a number of industries such as IQF food, Produce and Dairy.


BENEFITS


- 1 Lowest cost of ownership and lowest cost per pack
- 2 Easy access to all machine components Easy monitoring Fast change-over
- 3 Can handle thick films and guarantee tight seals for MAP applications
- Wide range of pack styles (pillow, BB, Quattro, Flexcan, Easypack, Shark pouch) and seal options (different hanghole, etc.)
- 5 Ultrasonics: drastic reduction of leak rate, film saving, energy saving



TECHNICAL DATA







Machine Speed	100 cpm
Wrapping Materials	Heat sealable materials (laminate, co-extruded, recyclable, etc.), polyethylene
Electronic Platform	Industrial B&R PLC and Allen Bradley PLC*
Program Memory	100+ programs
НМІ	12" HMI colour touch screen TFT and Allen Bradley*
Power Requirement	400 Vac+/-5%, 3 ph, neutral, GND, 50/60 Hz, 11.5 kW, 17.5 A
Compressed Air	up to 125 I/min at 6 bar, up to 400 I/min at 6 bar for LDPE
Electrical cabinet	Right-hand version, left-hand version*
Machine dimensions (W x D x H)	1606 x 2485 x1600 mm
Machine finishing	Stainless Steel
Machine Weight	1350 Kg
BAG DIMENSIONS	
Max. width	380 mm, 370 mm for LDPE
Min. width	50 mm (2")
Max. length**	480 mm (22.75")
FILM REEL DIMENSIONS	
Max. width	830 mm
Max. outer diameter	600 mm (23,75")
Core diameter	76 mm, 152 mm*

^{*} optiona

^{**} greater length feasible on request



