

Aseptic Filling in Bags Facilitates Validation

FS218 Aseptic Bag Filler

When product shelf-stability matters

There is a growing demand for aseptic filling of liquid products into containers without making use of hot fill or using preservatives and still maintaining an extended shelf life.

A frequent issue, especially on small scale, is the sampling, packaging and storage of products without introducing the risk of contamination.

The FS218 is the ideal solution if samples with extended shelf life are required.



Features & Benefits

- Compact design
- Suitable for a wide range of products
- Step-by-step instructions to ensure consistent aseptic conditions
- Seamless integration with OMVE HT220 or HT320 HTST/UHT systems
- No chemical sterilization of packaging, which minimizes risk of contamination

Applications

- Fruit & vegetable juices & purees
- Dairy products
- Desserts & puddings
- Baby food
- Soups & sauces
- Plant-based products

Working Principle

The pre-sterilized bag (sizes from 0,75-10 liters) is connected into the filling chamber. The small chamber separating the gland membrane to the product is steam flushed to clear out the air and then sterilized by steam. The top membrane of the gland is pierced to fill the bag. After filling, the bag is heat sealed. No chance of contamination during filling can occur.



Optional Accessories

- Electromagnetic flow meter
- 32mm filling gland (16mm standard)
- 15 liter buffer tank
- Brix meter
- Condensate flush
- Data logger

Specifications

Product code	FS218 Aseptic Bag-in-Box Filler
Bag sizes for filling cycle w/ 16mm gland	2 x 10 Liter bags/ min 3 x 4 Liter bags/ min 4 x 2 Liter bags/ min
Sterilization time	10-12 sec
Filling accuracy	+/- 1%
Filling temperature	Up to 80°C
Particles (soft)	<7mm
Filling controlled by	Two-hand control
Cleaning/ sterilization suitable	CIP/ SIP
Materials	
Product line	SS AISI 316
Frame	SS AISI 304
Weights & Dimensions	
Weight	210kg [462lbs]/ 247kg [544,5lbs] with buffer tank
L x W x H	920 x 830 x 2030mm [36,2 x 32,7 x 80"]/ 920 x 830 x 2630mm [36,2 x 32,7 x 103,5"] with buffer tank
Required utilities	
Electrical supply	200-240Vac/ 1ph+N+E/ 50Hz/ 16A or 200-240Vac/ 2ph+E/ 60Hz/ 16A
Compressed air	6-7bar(g) [87-100psi]
Steam	Max. 3,5bar(g) [51psi]
Water supply	Max. 3,5bar(g) [51psi]
Condensate	Drain

FS218 - Available in Two Versions



FS218 Filler	FS218 Filler with buffertank
Aseptic bag filler with CIP, SIP and flow control	Aseptic bag filler with CIP, SIP, buffer tank and flow control

FS

OMVE Netherlands B.V.
Gessel 61
3454 MZ, De Meern
The Netherlands
Tel +31 30 241 00 70
sales@omve.com
omve.com

OMVE Americas Inc.
251 Main Street East, Suite L01
Milton, ON L9T 1P1
Canada
Tel +1 416 986 8442
sales@omve.com
omve.com

Lab & Pilot Equipment 